

Link Vent 4000

4000 VENT

Equivalent Area Free Area Acoustic D_{n,e,w} (C; C_{tr}) dB- vent open Acoustic D_{n,e,w} (C; C_{tr}) dB- vent closed
 4000mm² EQA 3954.4mm² 32 (0;-1) 41 (0;0)

Draft acoustic data, to be finalised.

Internal				External								Ventilator			
Ventilator				Canopy				Grille (Timber, Sliding door, Sash)							
H (mm)	L (mm)	D (mm)	Weight (gram)	H (mm)	L (mm)	D (mm)	Weight (gram)	H (mm)	L (mm)	D (mm)	Weight (gram)	Attachment type	Rout H (mm)	Rout L (mm)	Stand W (mm)
18.5	380	15	21.32	18.5	380	25	39.90	20	383	5.8	9.84	Clip or Screw	13	348	14

EQUIVALENT AREA – 4000EQA

AIR LEAKAGE – 4000 vent **TBC** m³/h **TBC** L/s

WATERTIGHTNESS TEST TO BS EN 13141-1 – 5000 vent – Resistant to water penetration using method 1A meeting Class 9A requirement up to and at 750pa in BS EN 12208

DB RATING – Airbourne sound insulation to BS EN ISO 10140-1:2016 Annex E and BS EN ISO 10140-2:2010 and single number calculated in accordance with BS EN ISO 717-1:2013